



Swift Lift Interstore

'T' - 'TS' - 'L' Elevators

The Interstore range offer a machine for most applications being the most adaptable elevator available in the market place, by utilising a wide range of optional extras and variations.



Above: Bulk Hopper
Left: Circular Hopper
Right: Square Hopper
Below: Tipping Hopper

Model Specification

Interstore L range	4.50 m (14'9") to 7.50 m (24.6 ft) overall length.
L range delivery heights	1.00 m (39") minimum to 3.97 m (13') maximum
Interstore T range	9.00 m (29'6") to 12.00 m (39'6") overall length
T range delivery heights	1.00 m (39") minimum to 7.54 m (24'9") maximum



■ **'Swift Lift' Interstore elevators offer -**

A choice of 600 mm. (24 ins.) or 900 mm (36 ins) wide troughed and cleated endless rubber belts. with 35mm (1.5 in) high cleats.

■ **Choice of speeds**

Variable speed for regulated crop throughput and quality in all conditions. Fixed single or two speed motors for maximum throughput.

- Three phase, single phase or petrol engine drive.
- Electro hydraulic or hand hydraulic lift on the 'T' Range.
- 'Hand hydraulic, or simple variable pin height adjustment on the 'L' range



Swift Lift Interstore

'T' - 'TS' - 'L' Elevators

- The optional slewing platform on the 'TS' Range fills the store or bulker easily. Front wheels steered by hand-lever. Push-button power transmission for forward / backward movement and circular hopper supplied as standard.
- **Simple and robust machines.** One reason why 'Swift Lift elevators command premium prices on the secondhand market!
- 'Clean line' pressed steel frame for maximum safety and strength.
- Damage-free and spill-free high side fenders
- **Specialised Extras include.** Swivel and straight grain chutes, luffing head extension, castor wheel assembly, skate roller, conveyor to elevator coupling brackets and steel or canvas weather / dust covers.



A robust steel underchassis and chassis



Interstore 115T with a head extension working on wood chips